



KTEB-232LBF-1-TP-PIC	
Ballast Type	Electronic
Starting Method	Instant Start
Lamp Connection	Parallel
Input Voltage	120Vac ± 10%
Input Frequency	60Hz / 50Hz

ELECTRICAL SPECIFICATIONS:

Lamp Type	No. of Lamp	Input Watts	Input Current (Amps)	Power Factor	Crest Factor	Ballast Factor	Ballast Efficacy Factor	Max. THD %
F32T8	2	60	0.50	0.99	1.57	0.88	1.47	10
F32T8	1	38	0.32	0.99	1.55	1.10	2.89	10
F25T8	2	47	0.39	0.99	1.61	0.90	1.91	10
F25T8	1	31	0.26	0.99	1.52	1.10	3.55	10
F17T8	2	33	0.28	0.99	1.56	0.90	2.73	10
F17T8	1	22	0.19	0.98	1.52	1.10	5.00	10

PERFORMANCE:

- Sound Rated: A
- Minimum Starting Temperature: 0°F, -18°C
- Maximum Case Temperature: 167°F, 75°C
- Meets FCC Part 18 (Class B) Consumer Limits
- Transient Protection meets ANSI/IEEE C62.41 Cat. A
- Ballast frequency for all listed lamps: 20KHz-33KHz

APPROVALS:

- UL, cUL 935 listed

PHYSICAL DIMENSIONS:

Length (L):	9.50"	
Width (W):	1.38"	
Height (H):	1.18"	
Mounting(M):	8.90"	
Lead Length:		
White, Black	20"	
Blue	32X32"	
Red	48"	

WIRING DIAGRAM:

